

## For Commercial, Residential & Institutional HVAC Applications

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

# LEAD FREE\*

## Series LFDPG-3 Center Back-Entry Pressure Gauges

Dial Sizes: 1 1/2", 2"

Series LFDPG-3 Center Back-Entry Pressure Gauges are used in commercial, residential, and institutional HVAC applications. They feature ABS polymer cases, Kostil Polymer windows, 1/8" or 1/4" NPT connections, and copper alloy Bourdon tube sensing elements. The LFDPG-3 features Lead Free\* construction to comply with Lead Free\* installation requirements. Accuracy is ASME, Type B. Series LFDPG-3 gauges are available in various pressure rating scales. The dual scale features PSI and kPa measurements.



LFDPG-3

### Features

- ABS polymer case
- Kostil polymer window
- Copper alloy Bourdon sensing element
- Tin alloy welding
- 1/8" or 1/4" NPT connections
- ASME Type "B" accuracy

### Standards

ASME B40.100  
EN ISO 9001:2008  
EN ISO 14001:2004

### Temperature

Working Temperature: -4°F to 176°F (-20°C to 80°C)

### Materials

Case: ABS polymer  
Window: Kostil polymer  
Sensing Element: Copper alloy Bourdon tube  
Welding: Tin alloy  
Connection: Lead Free Brass

### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.


### NOTICE

Inquire with governing authorities for local installation requirements

\*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

## Dimensions – Weights



LEAD FREE	MODEL	SCALE		SIZE	DIMENSIONS				WEIGHTS	
					A		B			
				<i>in.</i>	<i>in.</i>	<i>mm</i>	<i>in.</i>	<i>mm</i>	<i>lbs.</i>	<i>kgs</i>
	LFDPG3-1½	0 – 160psi	1103 kPa	½	1½	38	1 <sup>9</sup> / <sub>16</sub>	40	.1	.05
	LFDPG3-2	0 – 60psi	413 kPa	¼	2	50	1 <sup>15</sup> / <sub>16</sub>	49	.2	.09
	LFDPG3-2	0 – 160psi	1103 kPa	¼	2	50	1 <sup>15</sup> / <sub>16</sub>	49	.2	.09
	LFDPG3-2	0 – 200psi	1379 kPa	¼	2	50	1 <sup>15</sup> / <sub>16</sub>	49	.2	.09

