Engineering Specification

Contractor

Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

CO-200

Line or Floor Cleanout

Specification

Watts CO-200 epoxy coated cast iron cleanout ferrule with 1/2"(13) thick gasketed cover.

Function

Job Name

Cleanout for installation on cast iron, PVC or ABS drain lines.

Call customer service if you need assistance with technical details.

Pipe Sizing		
Suffix	Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	

Cover		
Suffix	Description	
-1	5"(127) Dia., Nickel Bronze	
-4	5"(127) Dia., Ductile Iron	
-50	5"(127) Dia., Cast Iron	

Options		
Suffix	Description	
-6	Vandal Proof	
-13	All Galvanized	
-Z	Elastomeric Flange	

Optional Body Material		
Suffix	Description	
-60	PVC Body w/Socket Outlet	
-61	ABS Body w/Socket Outlet	





The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com Canada: T: (888) 208-8927 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com