Engineering Specification

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

FD-1100-C

Floor Drain with Round Stainless Steel Strainer

Specification

Watts FD-1100-C epoxy coated cast iron floor drain with membrane clamp, primary and secondary weepholes, and adjustable round Type 304 cast stainless steel strainer.

Call customer service if you need assistance with technical details.

Pipe Sizing		
Suffix	Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	
6	6"(152) Pipe Size	

Outlet Type			
Suffix	Description		
NH	No Hub (MJ)		
Р	Push On		
T	Threaded Outlet		
Х	Inside Caulk		

Strainer			
Suffix	Description		
5-3	5"(127) Dia. Stainless Steel		
6-3	6"(152) Dia. Stainless Steel		

Optional Body Material (NH Only)			
Suffix Description			
-60	PVC Body w/Socket Outlet		
-61	ABS Body w/Socket Outlet		

Options		
Suffix	Description	
-5	Sediment Bucket	
-6	Vandal Proof	
-8	Backwater Valve (3"/4" only)	
-10 Secured Top c/w Phillips Screws		
-13	-13 Galvanized Body	
-15 Strainer Extension (DD-50)		
-28	All Stainless Steel	
-113M	Special Epoxy From 3M Range	
-S0	Side Outlet	

8 1/8"(206)	-
5"(127), 6"(152)	Std. 1/2"(13) Reinforced Stainless Steel Strainer
See Chart A	Full 4"(102) Throat
	Membrane Clamp
	Primary Weepholes
See Chart B	Seepage —Collection Sump
	Serrated Flange
1/2"(13) NPT	pe Stop
Trap Primer Connection Pipe Size	33" Body ush-On Shown
01/54) 01/70) 41/400)	P" Push-On Gasket STM C-564)

		Chart A			
Str. Dia.	Min.	Max.	Load Rating	Free Area Sq. In.	
5"(127)	13/16"(21)	2 1/2"(64)	*XHD	6	
6"(152)	7/8"(22)	2 3/4"(70)	*XHD	7	

Chart	В

Pipe Size	Std. No Hub	P Push On	T Female Thread	X Inside Caulk	60/61 PVC/ ABS
2"(51)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
3"(76)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
4"(102)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	4"(102)
6"(152)	3 1/2"(89)				

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: T: (800) 338-2581 • Watts.com

Canada: T: (888) 208-8927 • Watts.ca

Latin America: T: (52) 55-4122-0138 • Watts.com

ES-WD-FD-1100-C-CAN 2344 © 2023 Watts