Engineering Specification

Job	Name
000	1 van i

Job Location

Engineer ____

Approval ____

Contractor _

Approval _

Contractor's P.O. No.

Representative

FD-870-P Standpipe Type Planting Area Drain

Specification

Watts FD-870-P standpipe type planting area drain with epoxy coated cast iron body, serrated clamping flange with integral double drainage weepholes and adjustable 4"(102) dia. ABS perforated standpipe and epoxy coated cast iron or chrome plated secured dome.

Call customer service if you need assistance with technical details.

Pipe Sizing		
Suffix	Description	
2	2"(51) Pipe Size	
3	3"(76) Pipe Size	
4	4"(102) Pipe Size	
6	6"(152) Pipe Size	

Outlet Type

Description

Suffix

Ρ

Т

Х

	Optional Body Material	
Suffix	Description	
-60	PVC Body w/Socket Outlet	
-61	ABS Body w/Socket Outlet	
*When s	pecifying Underdeck Clamp.	

6"(152) pipe size is not available.



Chart A

	Std.	Р	Т	X	60/61
Pipe Size	No Hub	Push On	Female Thread	Inside Caulk	PVC/ABS
2"(51)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
3"(76)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
4"(102)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	4"(102)
6"(152)	3 1/2"(89)				

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com Canada: T: (888) 208-8927 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com

NH No Hub (MJ) Push On **Threaded Outlet** Inside Caulk

Top Assembly		
Suffix	Description	
-1	Chrome Plated Dome	
-50	Cast Iron Dome	

Options		
Suffix	Description	
-10	Secured Top	
-10	c/w Phillips Screws	
-13	All Galvanized	
-42/ABS	Standpipe over 8", ABS	
-В	Sump Receiver	
-D	Underdeck Clamp**	
-S0	Side Outlet	