Engineering Specification

Job Name

Job Location

Engineer ____

Approval ___

Contractor _

Approval

Contractor's P.O. No.

Representative _

FD-870-TG Planting Area Drain with Deck Level **Drainage Grate**

Specification

Watts FD-870-TG planting area drain with epoxy coated cast iron body, membrane clamp, adjustable ballast guard riser section, epoxy coated ductile iron (standard) grate and no hub (MJ) (standard) outlet.

Call customer service if you need assistance with technical details.

Pipe Sizing			
Suffix	Description		
2	2"(51) Pipe Size		
3	3"(76) Pipe Size		
4	4"(102) Pipe Size		
6	6"(152) Pipe Size		

Outlet Type			
Suffix	Description		
NH	No Hub (MJ)		
Р	Push On		
Т	Threaded Outlet		
Х	Inside Caulk		

	Strainer	
Suffix	Description	
-1	8"(203), Nickel Bronze	
-3	8"(203), Stainless Steel Veneer	
-4	8"(203) Ductile Iron	
-		

Optional Body Material (NH Only)			
Suffix	Description		
-60	PVC Body w/Socket Outlet		
613	ABS Body w/Socket Outlet		
	,		

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • Watts.com Canada: T: (888) 208-8927 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com

	Options	
Suffix	Description	
-6	Vandal Proof	
-10	Secured Top c/w Phillips	
-10	Screws	
-12	Galvanized Top	
-13	All Galvanized	
-15	Adj. Extension (2", 2 3/4")	
-42	Perforated Standpipe	
-81	Bronze Dome	
-В	Sump Receiver	
-D	Underdeck Clamp**	
-S0	Side Outlet	



7 7/8



Epoxy Coated Heavy Duty Ductile Iron Grate (-42) 4"(102) ABS Perforated Standpipe (Optional) Auxiliary Drain Slots

Ballast Guard **Riser Sections**

Body Collar & Membrane Clamp

Weepholes

_"B3" Body Push-On Shown (P) Push-On Gasket (ÁSTM C-564)

2"(51), 3"(76), 4"(102) 6"(152) NH (MJ) (Standard)

	Std.	Р	т	X	60/61
Pipe Size	No Hub	Push On	Female Thread	Inside Caulk	PVC/ABS
2"(51)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
3"(76)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	3 3/4"(95)
4"(102)	3 5/8"(92)	4 1/4"(108)	4 1/4"(108)	4 1/2"(114)	4"(102)
6"(152)	3 1/2"(89)				